

TK-CLIMATE FLASH™

All Weather Flashing Tape

Item No. TK-2200

PRODUCT DESCRIPTION

TK-CLIMATE FLASH™ is a versatile, high performing air, moisture and vapor barrier that bonds to a wide variety of construction materials and stays put through a wide range of temperatures.

Features:

- Self-adhering air, moisture and vapor barrier.
- Self-seals around nails and staples.
- Durable and resistant to tears and puncturing.
- Low permeability.
- Conforms to irregular surfaces.
- Broad application temperature range from 5°F (-15°C) to 120°F (48°C).
- Cuts and applies easily with no special tools required for application.
- Compatible with the AIRMAX® line of air/vapor/weather barriers and CLIMATE TECH™ Weather Resistant System.

USES:

Suitable for interior or exterior use on commercial and residential applications. Adheres to construction materials such as: polyethylene, HouseWrap, metal, insulation, foam, fiberglass, fabrics, glass and plastics.

LIMITATIONS:

- When applying TK-CLIMATE FLASH™ in low temperatures (0°F-15°F), use of a Xylene primer is recommended.

STORAGE:

Store in a cool, dry area.

FIRST AID:

- Consult this product's safety data sheet for additional health and safety information. Safety Data Sheets are available through TK distributors, the TK office and the TK website.

AVAILABILITY:

TK-CLIMATE FLASH™ is available through TK Distributors. Contact TK Products for the nearest distributor.

TECHNICAL DATA

Composition and Materials:	A 100% solids formula of synthetic resins and thermoplastic cured butyl rubber coated on a polypropylene facer.
Packaging Configurations*:	Standard Widths: 4", 6", 9" Standard Length: 75'
A.I.M. Category:	This product is not currently regulated by 1999 Federal EPA VOC regulations

*Additional roll lengths and widths available.
Contact TK Products for more information.

TESTING DATA

Specification	Typical Value	Test Method
Adhesive Tape:	Acrylic	
Peel Adhesion - Anodized Aluminum	70 oz/in	PSTC-101
Peel Adhesion - Polyethylene	60 oz/in	PSTC-101
Peel Adhesion - Oriented Strand Board	60 oz/in	PSTC-101
Peel Adhesion - HouseWrap	50 oz/in	PSTC-101
Nail Sealability	Pass	ASTM E 331
Temperature Range	5°F to 176°F	
Flame Spread/Smoke Developed	5/25	ASTM E 84
Water Vapor Permeability	0.1866 Perms	ASTM E 96

FOR PROFESSIONAL USE ONLY

05/15 Last Rev. 11/13

CONDITIONS OF SALE/ LIMITED WARRANTY

TK Products, division of the Sierra Corporation, warrants that its products conform to the label descriptions, are free from manufacturing defects, and are fit for the ordinary purposes for which such goods are used. Inasmuch as the use of TK Products' product by others and other factors affecting product performance are beyond TK Products' control, TK Products does not guarantee the results to be obtained. There are no warranties except as stated herein, either express or implied, including implied warranties of merchantability or fitness for a particular purpose. SHOULD ANY TK PRODUCTS' PRODUCT FAIL TO GIVE SATISFACTORY RESULTS, TK PRODUCTS WILL REPLACE THE PRODUCT, OR AT ITS OPTION, REFUND THE PURCHASE PRICE. THIS IS THE SOLE AND EXCLUSIVE REMEDY FOR ANY FAILURE OF TK PRODUCTS' PRODUCTS TO PERFORM AS WARRANTED AND SHALL ALSO CONSTITUTE LIQUIDATED DAMAGES IN CASE OF LOSS. UNDER NO CIRCUMSTANCES SHALL THE BUYER BE ENTITLED TO ANY OTHER REMEDY OR DAMAGES. REMEDIES FOR INCIDENTAL AND CONSEQUENTIAL DAMAGES ARE SPECIFICALLY EXCLUDED. TK Products does not authorize any person to assume for it any other liability in connection with the sale or use of its products unless specifically authorized by TK Products in writing.

TK DISCLAIMER:

Every effort has been made to ensure the accuracy of the above information and to avoid infringement of any patent or copyright. The information is based on field tests by government and private agencies, as well as lab tests, and on technical data from raw material manufacturers. The person(s) specifying or requesting the use of these products is responsible for assuring their suitability for a specific use, as well as the proper application of the products. Where there is any question as to the suitability of a particular product, a small test patch is recommended. See also CONDITIONS OF SALE/ LIMITED WARRANTY (Section 7) above.



TK Products Construction Coatings

11400 West 47th Street Minnetonka, MN 55343

800-441-2129 toll free | 952-938-8084 fax | www.tkproducts.com