

# TK-BLOCK AND GRAFFITI GUARD 5220 VOC

## Water and Graffiti Resistant Coating

Item No. TK-5220 VOC

### PRODUCT DESCRIPTION

TK-BLOCK AND GRAFFITI GUARD 5220 VOC is a clear, silicone elastomer, water and graffiti resistant coating for protecting concrete block and other porous masonry surfaces. It provides excellent performance against damaging effects of water and weather, while also providing defense against graffiti and vandalization substances.

#### Features:

- Protects against exterior elements such as rain, sun and temperature extremes.
- Resists efflorescence and stains from moisture and mildew.
- Prevents penetration of most types of graffiti and provides quick and easy removal of these substances.
- Allows the surface to breathe and does not trap moisture.

### USES:

Suitable for exterior use on new or existing concrete block and other porous masonry materials.

### APPLICATION PROCEDURES

#### PREPARATION:

Protect surrounding surfaces including windows, aluminum, metal, glass and non-masonry substrates from contact with the product either directly or through its residue, fumes or spray mists. The surface should be clean, dry and porous. If necessary, use TK-CHEMICAL CLEANER 101\* and allow surfaces to dry completely prior to application. Any repairs, caulking or sealing should be complete and fully cured. New concrete should be allowed for cure for 28 days prior to application. Air and surface temperatures should be between 40°F - 90°F during application. Higher temperatures will affect product penetration due to solvent carrier evaporation. Always apply a test patch to check for surface qualification and desired results before continuing with application.

#### MIXING:

The product is supplied ready to use and should not be diluted. Keep the container tightly sealed until ready for use and stir thoroughly before applying.

NOTE: TK-BLOCK AND GRAFFITI GUARD 5220 VOC must be used immediately upon opening.

#### APPLICATION:

Low pressure spray (< 50 psi) is the preferred method of application, but the product may also be applied by brush or roller.

Spray Application - Fully saturate the surface spraying from the bottom to the top. For very porous surfaces, apply enough material to cause a 6"-8" run down. Avoid excessive overlapping and back roll any runs or drips. Avoid over application as this may cause surface darkening.

### TECHNICAL DATA

Color:	Clear
Weight/Gallon:	10.85 lbs
% Actives:	9%
Flash Point:	100°F
Dry Time	
To Touch:	25 minutes
Recoat/Light Traffic:	2 hours
A.I.M. Category:	Specialty Primers, Sealers and Undercoaters Maximum VOC 350 g/l

Brush or Roller Application - Fully saturate the surface. Avoid excessive overlapping and brush out any runs or drips.

Second Coat Application - Extremely porous surfaces may require a second coat for maximum graffiti protection. The second coat should be applied once the first coat is dry to the touch (or within 2 hours of the first coat).

#### CLEAN UP:

Clean tools and spills with mineral spirits before the material dries.

#### COVERAGE:

Surface	Coverage
Concrete block/Porous Masonry	30-125 square feet/gallon
Burnished block:	125 square feet/gallon

Coverage rates are provided as a guideline only. Many factors including surface texture, porosity and weather conditions will determine actual coverage rates.

#### LIMITATIONS:

- Do not apply to extremely dense, polished or painted surfaces.
- Do not apply to asphalt.
- Glass and non-masonry surfaces should be protected as this product may damage them.
- Not recommended for horizontal surfaces or below-grade applications.
- Stainless steel or brass fittings and gaskets should be used for spray application as the solvent may disintegrate other equipment.

#### FIRST AID:

- Consult this product's safety data sheet for additional health and safety information. Safety Data Sheets are available through TK distributors, the TK office and the TK website.

**AVAILABILITY:**

TK-BLOCK AND GRAFFITI GUARD 5220 VOC is available through TK Distributors. Contact TK Products for the nearest distributor.

Packaged in 5-gallon pails and 1-gallon cans.

FOR PROFESSIONAL USE ONLY

**NOTES:**

\*TK-CHEMICAL CLEANER must be purchased separately

11/08/18 Last Rev. 03/18

**CONDITIONS OF SALE/ LIMITED WARRANTY**

TK Products, division of the Sierra Corporation, warrants that its products conform to the label descriptions, are free from manufacturing defects, and are fit for the ordinary purposes for which such goods are used. Inasmuch as the use of TK Products' product by others and other factors affecting product performance are beyond TK Products' control, TK Products does not guarantee the results to be obtained. There are no warranties except as stated herein, either express or implied, including implied warranties of merchantability or fitness for a particular purpose. SHOULD ANY TK PRODUCTS' PRODUCT FAIL TO GIVE SATISFACTORY RESULTS, TK PRODUCTS WILL REPLACE THE PRODUCT, OR AT ITS OPTION, REFUND THE PURCHASE PRICE. THIS IS THE SOLE AND EXCLUSIVE REMEDY FOR ANY FAILURE OF TK PRODUCTS' PRODUCTS TO PERFORM AS WARRANTED AND SHALL ALSO CONSTITUTE LIQUIDATED DAMAGES IN CASE OF LOSS. UNDER NO CIRCUMSTANCES SHALL THE BUYER BE ENTITLED TO ANY OTHER REMEDY OR DAMAGES. REMEDIES FOR INCIDENTAL AND CONSEQUENTIAL DAMAGES ARE SPECIFICALLY EXCLUDED. TK Products does not authorize any person to assume for it any other liability in connection with the sale or use of its products unless specifically authorized by TK Products in writing.

**TK DISCLAIMER:**

Every effort has been made to ensure the accuracy of the above information and to avoid infringement of any patent or copyright. The information is based on field tests by government and private agencies, as well as lab tests, and on technical data from raw material manufacturers. The person(s) specifying or requesting the use of these products is responsible for assuring their suitability for a specific use, as well as the proper application of the products. Where there is any question as to the suitability of a particular product, a small test patch is recommended. See also CONDITIONS OF SALE/ LIMITED WARRANTY (Section 7) above.



**TK Products Construction Coatings**

11400 West 47th Street Minnetonka, MN 55343  
800-441-2129 toll free | 952-938-8084 fax | www.tkproducts.com