

TK-CONCRETE TREATING OIL 3102

Protective Concrete Coating

Item No.TK-3102

PRODUCT DESCRIPTION

TK-CONCRETE TREATING OIL 3102 is a high-build solution of boiled linseed oil and mineral spirits to be used as a protective coating for exterior concrete and masonry surfaces.

Features:

- Prevents spalling and deterioration of concrete in freezing temperatures.
- Provides long-term protection against water and chloride ion intrusion.
- Meets Minnesota, Wisconsin and Illinois Department of Transportation (DOT) specifications.

USES:

Suitable for exterior use on vertical or horizontal concrete bridge decks and parking structures.

APPLICATION PROCEDURES:

PREPARATION:

Surfaces must be clean and dry before applying TK-CONCRETE TREATING OIL 3102.

MIXING:

The material is supplied ready to use and requires no mixing or agitation prior to application.

APPLICATION:

Apply by spray or roller in a uniform manner and at the specified coverage rate.

CLEAN UP:

Use mineral spirits to clean tools and equipment. Pump solvent through the sprayer to remove residue of materials which can clog the hose and wand assembly.

COVERAGE:

Typical coverage rate is 200 square feet per gallon. Coverage rates are provided as a guideline only. Many factors including surface texture, porosity and weather conditions will determine actual coverage rates.

LIMITATIONS:

- Do not apply over acrylic cures and seals.

FIRST AID:

- Consult this product's safety data sheet for additional health and safety information. Safety Data Sheets are available through TK distributors, the TK office and the TK website.

TECHNICAL DATA

Composition and Materials:	Chlorinated rubber with a fast drying aromatic hydrocarbon solvent.
Color:	Amber-clear
Weight per Gallon:	7.55 lbs
Total Solids:	50%
Drying Time Tack Free: Open to Traffic:	4-6 hours 24 hours
VOC Content:	< 400 g/l
A.I.M. Category:	Concrete Protective Coatings Maximum VOC 400 g/l
Applicable Standards:	- MN DOT Spec. 3917.2 Type II - Wisconsin DOT Spec. - Illinois DOT Spec. - ASTM D-260 - ASTM D-235

AVAILABILITY:

TK-CONCRETE TREATING OIL 3102 is available through TK Distributors. Contact TK Products for the nearest distributor.

Packaged in 55-gallon drums and 5-gallon pails.

FOR PROFESSIONAL USE ONLY

03/15 Last Rev. 09/14

CONDITIONS OF SALE/ LIMITED WARRANTY

TK Products, division of the Sierra Corporation, warrants that its products conform to the label descriptions, are free from manufacturing defects, and are fit for the ordinary purposes for which such goods are used. Inasmuch as the use of TK Products' product by others and other factors affecting product performance are beyond TK Products' control, TK Products does not guarantee the results to be obtained. There are no warranties except as stated herein, either express or implied, including implied warranties of merchantability or fitness for a particular purpose. SHOULD ANY TK PRODUCTS' PRODUCT FAIL TO GIVE SATISFACTORY RESULTS, TK PRODUCTS WILL REPLACE THE PRODUCT, OR AT ITS OPTION, REFUND THE PURCHASE PRICE. THIS IS THE SOLE AND EXCLUSIVE REMEDY FOR ANY FAILURE OF TK PRODUCTS' PRODUCTS TO PERFORM AS WARRANTED AND SHALL ALSO CONSTITUTE LIQUIDATED DAMAGES IN CASE OF LOSS. UNDER NO CIRCUMSTANCES SHALL THE BUYER BE ENTITLED TO ANY OTHER REMEDY OR DAMAGES. REMEDIES FOR INCIDENTAL AND CONSEQUENTIAL DAMAGES ARE SPECIFICALLY EXCLUDED. TK Products does not authorize any person to assume for it any other liability in connection with the sale or use of its products unless specifically authorized by TK Products in writing.

TK DISCLAIMER:

Every effort has been made to ensure the accuracy of the above information and to avoid infringement of any patent or copyright. The information is based on field tests by government and private agencies, as well as lab tests, and on technical data from raw material manufacturers. The person(s) specifying or requesting the use of these products is responsible for assuring their suitability for a specific use, as well as the proper application of the products. Where there is any question as to the suitability of a particular product, a small test patch is recommended. See also CONDITIONS OF SALE/ LIMITED WARRANTY (Section 7) above.



TK Products Construction Coatings

11400 West 47th Street Minnetonka, MN 55343
800-441-2129 toll free | 952-938-8084 fax | www.tkproducts.com