

# TK-TRI-SHEEN ULTRA STAIN 5750

## Premium Wood and Concrete Stain

Item No. TK-5750 series

### PRODUCT DESCRIPTION

TK-TRI-SHEEN ULTRA STAIN 5750 is a low viscosity, opaque, premium stain designed specially for wood and concrete surfaces. TK-TRI-SHEEN ULTRA STAIN 5750 addresses common wood and concrete application problems to provide a durable and long-lasting decorative finish. Available in standard or custom color options.

#### Features:

- Holds back tannic acid bleed and offers superior grain crack resistance on wood surfaces.
- Reduces efflorescence staining/bloom on concrete surfaces.
- Provides superior surface penetration and adhesion as well as long-lasting color retention.
- Breathable film allows trapped moisture to pass through successfully without loosening or peeling the coating.
- Low odor and VOC compliant.

### USES:

Suitable for interior or exterior use on any properly prepared vertical wood, plywood, pressed board, concrete, precast, stucco, brick, block, stone or cementitious surfaces.

### APPLICATION PROCEDURES:

#### PREPARATION:

Surfaces should be dry and free from any foreign substances such as dirt, dust, wax, oil, curing compounds or efflorescence. Make certain the surface is free of any non-compatible matter by power washing, sand blasting or hand cleaning.

It is recommended that a 150 square foot test area be performed to check for visual and mechanical satisfaction, including color approval and proper adhesion before continuing with application.

#### APPLICATION:

Apply by spray, brush or roller. If airless spray is to be used, a tip size of .015"-.021" is recommended. Apply in a uniform and professional manner, maintaining a wet edge to prevent lap marks and using natural break points to prevent overlapping. Do not apply in a heavy, paint-like manner or apply enough material to cause puddling or mudcracking. A single, light coat is typically all that is needed; however, very porous surfaces may require a second coat.

New Concrete Surfaces - Concrete must be 28 days old (at minimum) and should have had adequate time to fully dry before applying this product. Consult TK Products for application recommendations where concrete surfaces are less than 28 days old. Repair any surface defects, and remove any laitance of efflorescence before applying. If a curing compound has been used, it must either be removed or have fully dissipated. The surface pH should be tested, and must be at 12 or below at the time of application.

### TECHNICAL DATA

Composition and Materials:	Comprised of 100% acrylic resins for superior adhesion and utilizes the latest in resin technology. Only inorganic pigments are used to ensure long-term color retention.
Gloss:	5 @ 60°
Dry Film Thickness:	2.0-2.5 mils
Dry Time (at 70°F & 50%RH)	
To Touch:	30-45 minutes
Recoat/Light	2 hours
Traffic:	24-48 hours
Full Cure:	
VOC Content:	< 250 g/l
A.I.M. Category:	Flat Coatings, Exterior Maximum VOC 250 g/l

\*Cooler temperatures and higher humidity rates will extend dry times

### CLEAN UP:

Clean tools, spray equipment and spills with soap and water before the material dries.

### COVERAGE:

Surface	Coverage
Wood	200 sq.ft./gal
Concrete	200-300 sq.ft./gal

Coverage rates are provided as a guideline only. Many factors including surface texture, porosity and weather conditions will determine actual coverage rates.

### LIMITATIONS:

- Not for use on horizontal surfaces.
- Do not apply to frozen and/or frost covered surfaces.
- Ambient and substrate temperatures should be above 40°F at the time of application and throughout the cure time of the coating.
- It is recommended that the coating be allowed 24 hours of cure time before being exposed to rain as heavy rain or down bursts may cause wash off of the material if not fully cured.
- A moisture test is recommended before applying this product. Do not apply if the moisture content is higher than 17%.

### FIRST AID:

- Consult this product's safety data sheet for additional health and safety information. Safety Data Sheets are available through TK distributors, the TK office and the TK website.

**AVAILABILITY:**

TK-TRI-SHEEN ULTRA STAIN 5750 is available through TK Distributors. Contact TK Products for the nearest distributor.

Available in standard colors or custom colors may be produced upon request (allow 2-3 weeks for custom colors to be produced). Please submit color standards for pricing.

Packaged in 250-gallon totes, 55-gallon drums and 5-gallon pails.

FOR PROFESSIONAL USE ONLY

07/16 Last Rev. 04/15

**CONDITIONS OF SALE/ LIMITED WARRANTY**

TK Products, division of the Sierra Corporation, warrants that its products conform to the label descriptions, are free from manufacturing defects, and are fit for the ordinary purposes for which such goods are used. Inasmuch as the use of TK Products' product by others and other factors affecting product performance are beyond TK Products' control, TK Products does not guarantee the results to be obtained. There are no warranties except as stated herein, either express or implied, including implied warranties of merchantability or fitness for a particular purpose. SHOULD ANY TK PRODUCTS' PRODUCT FAIL TO GIVE SATISFACTORY RESULTS, TK PRODUCTS WILL REPLACE THE PRODUCT, OR AT ITS OPTION, REFUND THE PURCHASE PRICE. THIS IS THE SOLE AND EXCLUSIVE REMEDY FOR ANY FAILURE OF TK PRODUCTS' PRODUCTS TO PERFORM AS WARRANTED AND SHALL ALSO CONSTITUTE LIQUIDATED DAMAGES IN CASE OF LOSS. UNDER NO CIRCUMSTANCES SHALL THE BUYER BE ENTITLED TO ANY OTHER REMEDY OR DAMAGES. REMEDIES FOR INCIDENTAL AND CONSEQUENTIAL DAMAGES ARE SPECIFICALLY EXCLUDED. TK Products does not authorize any person to assume for it any other liability in connection with the sale or use of its products unless specifically authorized by TK Products in writing.

**TK DISCLAIMER:**

Every effort has been made to ensure the accuracy of the above information and to avoid infringement of any patent or copyright. The information is based on field tests by government and private agencies, as well as lab tests, and on technical data from raw material manufacturers. The person(s) specifying or requesting the use of these products is responsible for assuring their suitability for a specific use, as well as the proper application of the products. Where there is any question as to the suitability of a particular product, a small test patch is recommended. See also CONDITIONS OF SALE/ LIMITED WARRANTY (Section 7) above.



**TK Products Construction Coatings**

11400 West 47th Street Minnetonka, MN 55343  
800-441-2129 toll free | 952-938-8084 fax | [www.tkproducts.com](http://www.tkproducts.com)