

FEBRUARY 1, 2010

## **TK-9010 EPOXY CRACK & JOINT FILLER**

### ***Product Information Statement for LEED® New Construction (NC) Version 2.2 Credit Documentation***

TK-9010 EPOXY CRACK & JOINT FILLER is a fast set, two-component epoxy/amine for filling cracks and control joints in concrete. TK-9010 EPOXY CRACK & JOINT FILLER is flexible but tensile enough to hold up to fork lift and wheel traffic. The fast cure allows areas to be re-opened in minimal time.

***TK Products certifies the following information for TK-9010 EPOXY CRACK & JOINT FILLER:***

#### **Manufacturing Location**

TK-9010 EPOXY CRACK & JOINT FILLER is manufactured in Minnetonka, MN.

#### **Regional Materials**

20% by weight of TK-9010 EPOXY CRACK & JOINT FILLER was produced with regionally extracted and processed materials.

#### **Recycled Content**

TK-9010 EPOXY CRACK & JOINT FILLER is manufactured with 6% combined recycled content.

#### **VOC Content**

TK Products certifies that the VOC (volatile organic content) of TK-9010 EPOXY CRACK & JOINT FILLER is 0g/l.

***Based upon the above information, TK Products certifies that TK-9010 EPOXY CRACK & JOINT FILLER may contribute to the following LEED NC v2.2 Credits:***

- MR Credits 1.1 & 1.2: Building Reuse: Maintain 75% & 95% of Existing Walls, Floors, & Roof
- MR Credits 4.1 & 4.2: Recycled Content: 10% & 20% (post-consumer + ½ pre-consumer)
- MR Credits 5.1 & 5.2: Regional Materials: 10% & 20% Extracted, Processed, & Manufactured

Respectfully,



LEED Administrator  
TK Products  
Tel: 800-441-2129

*LEED is a trade mark of the US Green Building Council*