



TK-SALT PROTECTOR PLUS WB

Water-Borne Deep Penetrating Water & Salt Repellent

Item No. TK-290 WB 05

PRODUCT DESCRIPTION

TK-SALT PROTECTOR PLUS WB is a ready-to-use, water-borne, VOC compliant, deep penetrating, silane/siloxane blend that acts as an impenetrable barrier against the intrusion of water and chloride ions (salt) into concrete and masonry surfaces.

Features:

- Extremely low VOC content and virtually odor-free.
- Low viscosity for deep penetration into the substrate and elimination of surface moisture which can lead to spalling, freeze damage and rebar corrosion.
- Forms a permanent bond with the substrate to provide uniform protection against damage due to water and deicing chemicals, acid rain, freeze/thaw exposure, airborne dirt, smog, industrial fumes and most other atmospheric chemicals.
- Outperforms typical water repellents which can only bond physically with the surface and thus provide only marginal protection.
- The coating is colorless, non-staining and non-yellowing.

USES:

Suitable for above-grade surfaces, vertical or horizontal.

Use to protect any concrete, burnish block, CMU, single wythe, masonry or cementitious surface. Applications include parking structures, bridge decks and ramps, piers and pilings, precast concrete, poured concrete walls, natural and synthetic stone, burnish block, split face block, stucco and clay brick.

**This product is not suitable for use on gypsum, glazed brick or block which will be painted over.*

APPLICATION PROCEDURES:

PREPARATION:

Before using this product, read the Safety Data Sheet for complete safety information.

New Concrete - It is best practice to allow new concrete surfaces 2-4 weeks to cure before treating with this product. Remove any coarse particles or dust with a brush or with compressed air. Only impregnate concrete that has a uniformly dry surface with no damp spots or patches.

Existing Concrete: - Weathered or dirty surfaces should be cleaned using superheated steam or by power-washing.

A test patch should always be performed to determine proper results and coverage rates prior to application.

MIXING:

The material is ready for use and requires no mixing. Do not thin or dilute.

APPLICATION:

Apply by roller or spray equipment in a uniform manner and in sufficient quantity to completely wet out the substrate with a minimum of 2" run down. Avoid puddling on horizontal surfaces. Very porous surfaces may require two coats.

Decorative/Integrally Colored Block application - When applying to decorative block or substrates where darkening of the surface is undesirable, apply only to the point of saturation (no run down).

CLEAN UP:

Clean tools, equipment and spills with warm soapy water.

COVERAGE:

Surface	Coverage
Most Concrete and Masonry (substrate dependent):	50-200 square feet/gallon
Parking Structures and Bridge Decks:	125 square feet/gallon

Coverage rates are provided as a guideline only. Many factors including surface texture, porosity and weather conditions will determine actual coverage rates.

TECHNICAL DATA	
Composition and Materials:	A water borne, silane/siloxane blend.
Active Solids (%):	5%
Flash Point:	> 200°F
VOC Content*:	< 20 g/l
A.I.M. Category:	Low Solids Coating Maximum VOC 120 g/l
Applicable Standards:	- ASTM C666 Resistance of Concrete to Rapid Freezing and Thawing - ASTM C672 Scaling Resistance - NCHRP 244 (water absorption, % water vapor transmission and % reduction in chloride intrusion)

MAINTENANCE:

If wear patterns occur, TK-SALT PROTECTOR PLUS WB may be reapplied to affected areas.

LIMITATIONS:

- KEEP FROM FREEZING.
- Do not use below-grade or under hydrostatic pressure.
- Do not apply if substrate temperature is below 40°F for 24 hours prior to treatment.
- Over application may cause darkening or discoloration of the surface.
- Application to inappropriate or non-compatible substrates may affect adhesion of subsequent coatings.

PROTECTION OF VEGETATION, GLASS AND ALUMINUM SURFACES:

Avoid contact with live vegetation, glass and aluminum. If properly protecting these surfaces is impractical, the following steps should be performed:

- 1) Minimize contact of TK-SALT PROTECTOR PLUS WB with live vegetation, glass and aluminum surfaces.
- 2) If TK-SALT PROTECTOR PLUS WB comes into contact with glass or aluminum, thoroughly clean surfaces with Windex® or an ammonia cleaner while the material is still wet.

FIRST AID:

- Consult this product's safety data sheet for additional health and safety information. Safety Data Sheets are available through TK distributors, the TK office and the TK website.

AVAILABILITY:

TK-SALT PROTECTOR PLUS WB is available through TK Distributors. Contact TK Products for the nearest distributor.

Packaged in 55-gallon drums, 5-gallon pails and 1-gallon cans.

FOR PROFESSIONAL USE ONLY

03/16 Last Rev. N/A

CONDITIONS OF SALE/ LIMITED WARRANTY

TK Products, division of the Sierra Corporation, warrants that its products conform to the label descriptions, are free from manufacturing defects, and are fit for the ordinary purposes for which such goods are used. Inasmuch as the use of TK Products' product by others and other factors affecting product performance are beyond TK Products' control, TK Products does not guarantee the results to be obtained. There are no warranties except as stated herein, either express or implied, including implied warranties of merchantability or fitness for a particular purpose. **SHOULD ANY TK PRODUCTS' PRODUCT FAIL TO GIVE SATISFACTORY RESULTS, TK PRODUCTS WILL REPLACE THE PRODUCT, OR AT ITS OPTION, REFUND THE PURCHASE PRICE. THIS IS THE SOLE AND EXCLUSIVE REMEDY FOR ANY FAILURE OF TK PRODUCTS' PRODUCTS TO PERFORM AS WARRANTED AND SHALL ALSO CONSTITUTE LIQUIDATED DAMAGES IN CASE OF LOSS. UNDER NO CIRCUMSTANCES SHALL THE BUYER BE ENTITLED TO ANY OTHER REMEDY OR DAMAGES. REMEDIES FOR INCIDENTAL AND CONSEQUENTIAL DAMAGES ARE SPECIFICALLY EXCLUDED.** TK Products does not authorize any person to assume for it any other liability in connection with the sale or use of its products unless specifically authorized by TK Products in writing.

TK DISCLAIMER:

Every effort has been made to ensure the accuracy of the above information and to avoid infringement of any patent or copyright. The information is based on field tests by government and private agencies, as well as lab tests, and on technical data from raw material manufacturers. The person(s) specifying or requesting the use of these products is responsible for assuring their suitability for a specific use, as well as the proper application of the products. Where there is any question as to the suitability of a particular product, a small test patch is recommended. See also CONDITIONS OF SALE/ LIMITED WARRANTY (Section 7) above.